



# RAPTOR LINER - TINTABLE (RLT-US)

## Safety Data Sheet RLT-US

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 08/10/2015

Revision date: 11/22/2017

Supersedes: 10/31/2017

Version: 4.0

## DRIVING SURFACE PERFECTION

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : RAPTOR LINER - TINTABLE (RLT-US)  
Product group : Coating  
Other means of identification : UP0821, UP0821V, UP0823, UP4802, UP4804, UP4851

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

U-POL US Inc  
108 Commerce Way  
Stockertown PA 18083 - USA  
T 1-800-340-7824 - F 1-800-787-5150  
[technical.department@u-pol.com](mailto:technical.department@u-pol.com) - [www.u-pol.com](http://www.u-pol.com)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC - 1-800-424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flam. Liq. 2 H225  
Eye Irrit. 2 H319  
Skin Sens. 1 H317  
Carc. 1A H350  
STOT SE 3 H336  
Aquatic Chronic 3 H412

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

GHS07

GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapour  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H350 - May cause cancer  
H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking.  
P261 - Avoid breathing fume, spray, vapors.  
P264 - Wash hands thoroughly after handling.  
P280 - Wear face protection, protective clothing, protective gloves.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

#### 2.3. Other hazards

No additional information available

# RAPTOR LINER - TINTABLE (RLT-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Acetone	(CAS-No.) 67-64-1	5 - 23	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)		< 5	Skin Sens. 1, H317 Aquatic Chronic 2, H411
reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	(CAS-No.) 1065336-91-5	< 5	Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
cristobalite, 1%=<conc respirable crystalline silica<10%	(CAS-No.) 14464-46-1	< 5	Carc. 1A, H350

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Dry sand. Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Reactivity	: Highly flammable liquid and vapour.

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Safety glasses. Protective clothing.
Emergency procedures	: Avoid contact with skin and eyes. Do not breathe vapors. No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing vapors, fume, spray.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

# RAPTOR LINER - TINTABLE (RLT-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage. Contain leaking substance.
- Methods for cleaning up : Take up liquid spill into absorbent material. This material and its container must be disposed of in a safe way, and as per local legislation. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Keep away from Heat-ignition. - No smoking.
- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid breathing vapors, fume, spray. Avoid contact with skin and eyes.
- Hygiene measures : Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Ground/bond container and receiving equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
- Storage temperature : < 25 °C
- Storage area : Store in well ventilated area.
- Special rules on packaging : Keep only in original container.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

RAPTOR LINER - TINTABLE (RLT-US)		
ACGIH	Not applicable	
OSHA	Not applicable	
Acetone (67-64-1)		
ACGIH	ACGIH TWA (ppm)	250 ppm
ACGIH	ACGIH STEL (ppm)	500 ppm
ACGIH	Remark (ACGIH)	eye irr; CNS impair; BEI
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
reaction mass of $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)		
ACGIH	Not applicable	
OSHA	Not applicable	

# RAPTOR LINER - TINTABLE (RLT-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)

ACGIH	Not applicable
OSHA	Not applicable

### crystalobalite, 1%=<conc respirable crystalline silica<10% (14464-46-1)

ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	0.025 mg/m <sup>3</sup> (Silica-Crystalline Cristobalite; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Respirable fraction)
OSHA	Remark (OSHA)	(3) See Table Z-3.

## 8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station.  
Personal protective equipment : Gas mask. Gloves. Protective clothing. Safety glasses.



- Materials for protective clothing : Impermeable clothing.  
Hand protection : Protective gloves.  
Eye protection : Safety glasses.  
Skin and body protection : Wear suitable protective clothing.  
Respiratory protection : Air-fed respiratory protective equipment should be worn when this product is sprayed. Wear respiratory protection.  
Environmental exposure controls : Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid  
Appearance : Viscous. Liquid.  
Color : Beige  
Odor : aromatic  
Odor threshold : No data available  
pH : No data available  
Relative evaporation rate (butyl acetate=1) : No data available  
Melting point : Not applicable  
Freezing point : No data available  
Boiling point : > 35 °C  
Flash point : < 0 °C  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Flammability (solid, gas) : No data available  
Vapor pressure : No data available  
Relative vapor density at 20 °C : No data available  
Relative density : No data available  
Specific gravity / density : 1.1 - 1.14 g/cm<sup>3</sup>  
Solubility : insoluble in water. soluble in most organic solvents.  
Log Pow : No data available  
Log Kow : No data available  
Viscosity, kinematic : No data available  
Viscosity, dynamic : No data available  
Explosive properties : No data available  
Oxidizing properties : No data available  
Explosion limits : No data available

# RAPTOR LINER - TINTABLE (RLT-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 9.2. Other information

VOC content - Actual : 218 g/l  
VOC content - Regulatory : 293 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

No flames, no sparks. Eliminate all sources of ignition. Avoid contact with hot surfaces. Heat.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified  
  
Skin corrosion/irritation : Not classified  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitization : May cause an allergic skin reaction.  
Germ cell mutagenicity : Not classified  
Carcinogenicity : May cause cancer.

#### **crystalobalite, 1%=<<conc respirable crystalline silica<10% (14464-46-1)**

IARC group	1 - Carcinogenic to humans
------------	----------------------------

Reproductive toxicity : Not classified  
Specific target organ toxicity – single exposure : May cause drowsiness or dizziness.  
  
Specific target organ toxicity – repeated exposure : Not classified  
  
Aspiration hazard : Not classified  
Symptoms/effects after skin contact : May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

#### **crystalobalite, 1%=<<conc respirable crystalline silica<10% (14464-46-1)**

Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

# RAPTOR LINER - TINTABLE (RLT-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.3. Bioaccumulative potential

#### crystalobalite, 1%=<conc respirable crystalline silica<10% (14464-46-1)

Bioaccumulative potential : No test data available.

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the ozone layer : No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Additional information : Flammable vapors may accumulate in the container.

## SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, II

UN-No.(DOT) : UN1263

Proper Shipping Name (DOT) : Paint  
including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).  
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.  
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / 1 + a (tr - tf)$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.  
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).  
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Packaging Non Bulk (49 CFR 173.xxx) : 173

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

# RAPTOR LINER - TINTABLE (RLT-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

### Additional information


Other information : No supplementary information available.

### ADR

Transport document description : UN 1263 PAINT RELATED MATERIAL, 3, II, (D/E)  
Packing group (ADR) : II  
Class (ADR) : 3 - Flammable liquid  
Hazard identification number (Kemler No.) : 33  
Classification code (ADR) : F1  
Hazard labels (ADR) : 3 - Flammable liquids



Orange plates :



Tunnel restriction code (ADR) : D/E  
LQ : 5I  
Excepted quantities (ADR) : E2

### Transport by sea

UN-No. (IMDG) : 1263  
Proper Shipping Name (IMDG) : PAINT  
Class (IMDG) : 3 - Flammable liquids  
Packing group (IMDG) : II - substances presenting medium danger

### Air transport

UN-No. (IATA) : 1263  
Proper Shipping Name (IATA) : Paint  
Class (IATA) : 3 - Flammable Liquids  
Packing group (IATA) : II - Medium Danger

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### Acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Not subject to reporting requirements of the United States SARA Section 313

CERCLA RQ : 5000 lb

**reaction mass of  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)**

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

**reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)**

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. International regulations

#### CANADA

# RAPTOR LINER - TINTABLE (RLT-US)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

No additional information available

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225  
Eye Irrit. 2 H319  
Skin Sens. 1 H317  
STOT SE 3 H336  
Aquatic Chronic 3 H412  
Full text of H statements : see section 16

### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

#### 15.2.2. National regulations

**reaction mass of  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -hydroxypoly(oxyethylene) and  $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)**

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

**reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)**

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

## SECTION 16: Other information

Revision date : 11/22/2017

Full text of H-phrases:

H225	Highly flammable liquid and vapour
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H350	May cause cancer
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard


: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard

: 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.

NFPA reactivity

: 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



SDS US UPOL

*For professional use only.*

*The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.*